

DH-IPC-DB665

D1 Vandal-proof Network Dome Camera



Features

- 1/3" SONY Super HAD CCD
- H.264 dual-stream encoding
- 25/30fps@D1/HD1/CIF/QVGA resolution
- D&N, 2DNR, AWB, AGC, BLC,
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Built-in 1/1 alarm in/out
- 6mm fixed lens (3.6mm,8mm,12mm optional)
- Micro SD memory, IP65, IK10, PoE,

DH-IPC-DB665


Technical Specifications

Model	DH-IPC-DB665P	DH-IPC-DB665N
Camera		
Image Sensor	1/3" SONY Super HAD CCD	
Effective Pixels	795(H)x596(V)	811(H)x508(V)
Scanning System	Interlacing	
Electronic Shutter Speed	Auto/Manual 1/25~1/10000	Auto/Manual 1/30~1/10000
Min. Illumination	0.1LUX/F1.2	
S/N Ratio	> 50dB	
Video Output	1 channel BNC(1.0Vp-p, 75Ω)	
Camera Features		
Day/Night	Auto(Electronic) / Color / B/W	
Backlight Compensation	BLC	
White Balance	Auto	
Gain Control	Auto	
Noise Reduction	2D	
Privacy Masking	Up to 4 areas	
Lens		
Focal Length	6mm (3.6mm,8mm,12mm optional)	
Max Aperture	F1.8	
Focus Control	Fixed lens	
Angle of View	H: 42° (70°/46°/35°)	
Lens Type	Fixed/ Fixed Iris	
Mount Type	Board-in Type	
Video		
Compression	H.264	
Resolution	D1(704×576) /HD1(704x288)/ CIF(352×288)/QVGA(320×240) /QCIF(176x144)/QQVGA(160x120)	D1(704×480) /HD1(704x288) CIF(352×240) / QVGA(320×240) /QCIF(176x120)/QQVGA(160x120)
Frame Rate	Main Stream	D1/HD1/CIF(1 ~ 25/30fps)
	Sub Stream	D1/HD1/CIF/QVGA/QCIF/QQVGA(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 4096Kbps	
Audio		
Compression	G.711a/G.711u(64kbps)/PCM(128kbps)/AMR(64kbps)	
Interface	1 /1 channel In/Out	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	IPv4, HTTP, SSL, TCP/IP, UDP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter,	
ONVIF	ONVIF Ver. 2.0	
Max. User Access	10 users	

DH-IPC-DB665

Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 32GB
Alarm	2/1 channel in/out
General	
Power Supply	DC12V, PoE(802.3af)
Power Consumption	<5W
Working Environment	-10°C~+55°C, 10%~90%
Protection Level	IP65, IK10
Dimensions	Φ141mm×120mm
Weight	350kg

Dimensions (mm)



<http://www.asi.ind.in>

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.