

DS-6101DI Digital Video Server



Key Features

- H.264 /MPEG4 video compression
- Third-party network cameras supported
- Up to 4CIF resolution decoding
- TCP, UDP, MCAST and RTP transmission protocols

Rear Panel of DS-6101DI



1. PWR, power LED indicator
2. LINK, network connection status LED indicator
3. RX/TX, data transmitting/receiving status LED indicator
4. RESET, reset to the default parameters
5. VIDEO OUT, BNC video output



1. MIC IN, voice talk input
2. Audio out
3. RS-232 serial interface
4. RS-485 serial interface
5. Alarm in/ alarm out(4 inputs/2 outputs)
6. LAN, 10/100/1000Mbps self-adaptive UTP Ethernet interface
7. 12VDC power input
8. GND, grounding

Specifications

	DS-6101DI
IP video input	H.264 / MPEG4
Decoding resolution	4CIF / DCIF / 2CIF / CIF / QCIF
Video output	1-ch CVBS output, resolution: 704x576 (PAL); 704x 480 (NTSC)
Frame rate	25 fps (P) /30 fps (N)
Stream type	Video, Video & Audio
Video bit rate	2M-12M adjustable (bps)
Audio output	1-ch, RCA (2.0~2.4 Vp-p, 600 Ω)
Voice talk input	1-ch, 3.5 mm audio interface (2.0~2.4 Vp-p, 1 kΩ)
Communication Interface	1 RJ45 10M /100M /1000M self-adaptive Ethernet interface 1 RJ45 RS-232 port, 1 RJ45 RS-485 port
Alarm in	4
Alarm out	2
Power Supply	12 VDC
Consumption	12 W
Working Temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working Humidity	10%~90%
Dimensions (W × D × H)	198 × 123 × 39 mm
Weight	1.5 kg