

# MD08W-N

8 channel H.264 DVR

 **MAXIMUS**  
Max Security. Max Technology.



## Key Features

- 8 Channel simultaneous Playback
- Pentaplex Function
- Mobile Viewing – Supports Symbian, Android, Windows & iPhone
- Dual stream support
- Strong CMS software
- Support SD Card



## Specifications:

Format	H.264 main profile
Master processor	Technical grade embedded micro controller
O.S.	Embedded Linux operation
System resources	Pentaplex Function
Operation interface	16bit true color graphical operation interface, support mouse operation, Remote
Video standard	PAL (625TVLine, 50fps); NTSC (525TVLine, 60fps)
Monitoring quality	PAL, D1 (704x576); NTSC, D1 (704x480)
Playback quality	PAL, CIF (352x288); NTSC, CIF (352x240)(real-time) PAL, D1 (704x576); NTSC,
Code capacity	CIF: 200FPS PAL, 240fps NTSC; D1: 100fps PAL, 120 fps NTSC;
Motion detection	64(8X8) surveyed area can be set in everyone frame; Multilevel sensitivity can be set
Audio compression	G711A
VoIP	Yes
Recording mode	Manual/alarm/motion detection/timing
Local playback	Single channel, 8 channel (max 8 channel simultaneously)
Playback Function	Play, Pause, Stop, Rewind, Fast Forward, Slow Forward, Next file, Repeat Playback, Full
Recording search	Time point, calendar, event, channel
Picture display	1/4/8/9 frame
VGA Resoution	800*600, 1024*768, 1280*720, 1280*1024, 1360*768, 1440*900
Simultaneous View(TV/VGA)	yes
Occupation HDD space in everyone channel	Audio: 28.8Mbyte/ hour + video: 25~450Mbyte/hour
Record storage	Local HDD, and network

HDD Accomodation	2 HDD, 1 HDD + 1 DVD
SD card	yes
Backup mode	Network, USB HDD, DVD-R/RW
Video input	8 channel BNC
Video output	1 channel BNC (1.0Vp-p, 75 ohm), 1 channel VGA output
Audio input	8channel RCA
Audio output	1 channel RCA
Alarm input	8channel
Alarm output	1 channel
Ethernet	RJ45 10M/100M self-adapting Ethernet port,
PTZ	1 x RS485
USB	2 x USB interface
HDD	2 x SATA supports
Network Services	PPPOE, NTP, EMAIL, IPFILTER, FTP, DDNS, ARSP, ALARM SERVER, MOBILE MONITOR,
Network Remote Connection	I.E. viewing, and supports Windows mobile, Symbian, iPhone, Black Berry and Android
Power	12V/4.00A Power adaptor
Dissipation	<10W(w/o HDD)
Working temperature	0 degree +- 55 degree
Working humidity	10% -90 %
Dimension	Color box: 410*415*135mm, DVR: 353*325*61 mm Carton: 580*380*340mm,
Weight	3.7KG/carton
Support language	English, French, Portugal, Russia, Italian, Spanish, Thai, Greek, Japanese, German, Turkish, Polski ,Finnish,Farsi Vietnamese,Romanian and Hungarian.