## CP-DY48L2H1



## IR Dome Camera - 20 Mtr



480

Elvl

1/3" CCD

CCD

AGC

## **Main Features**

- $\Rightarrow~1/3$  " Sony Super HAD II CCD
- $\Rightarrow$  480TVL Standard Resolution Camera
- $\Rightarrow\,$  0 lux @ F1.2 (IR ON)
- $\Rightarrow\,$  3.6 mm Fixed Lens
- $\Rightarrow\,$  IR Range of 20 Mtrs with 24 LED's
- $\Rightarrow\,$  AGC, AWB, BLC
- $\Rightarrow\,$  CE, FCC and RoHS Certified

Mage Sensor1/3" Sony Super HAD II CCDPixelsPAL:S37HxS97V, NTSC:S37Hx505VResolution480 TVLMin. Illumination0 lux @F1.2S/N Ratiomore than 48dBElectronic Shutter1/50(1/60) - 1/100000 SecElectronic Shutter1/50(1/60) - 1/100000 SecElectronic Shutter0.45Samma Correction0.45Samma Correction0.45Samma Correction0.N/OFF SelectableBack Light Compensation0.N/OFF SelectableR24 LEDs, Upto 20 MtrsSyncInternalVideo Output1.0 Vp-p/75 ohmPower Consumption <sw< td="">Power ConsumptionSyncDimensions75 x 92Weight260Operating Temperature-10~50 °C</sw<>	Auto Gain Control White Balance	Backlight Compensation Day& Night
PhielsPAL:537Hx597V, NTSC:537Hx505VResolution480 TVLMin. Illumination0 lux @F1.2S/N Ratiomore than 48dBElectronic Shutter1/50(1/60) - 1/100000 SecElectronic Shutter3.6 mmFlickerless ModeYesSamma Correction0.45Samma Correction0.45Samma Correction0.N/OFF SelectableBack Light Compensation0.N/OFF SelectableSyncInternalVideo Output1.0 Vp-p/75 ohmPower Consumption75 x 92Dimensions75 x 92Weight260Operating Temperature-10~50 °C	Feature	Specification
Resolution480 TVLMin. Illumination0 lux @F1.2S/N Ratiomore than 48dBElectronic Shutter1/50(1/60) - 1/10000 SecFlickerless ModeYesLens3.6 mmGamma Correction0.45AutoMite Balance (AWB)Back Light CompensationON/OFF SelectableR24 LEDs, Upto 20 MtrsSyncInternalVideo Output0.10 Vp-p/75 ohmPower Consumption5% 92Power Consumption5x 92Weight260Operating Temperature10~50 °C	Image Sensor	1/3" Sony Super HAD II CCD
Min. Illumination0 lux @F1.2S/N Ratiomore than 48dBElectronic Shutter1/50(1/60) - 1/10000 SecFlickerless ModeYesLens3.6 mmGama Correction0.45White Balance (AWB)AutoBack Light CompensationON/OFF SelectableBack Light CompensationON/OFF SelectableSyncInternalVideo Output0.10 Vp-p/75 ohmPower ConsumptionSyncPower ConsumptionSyncOniconside SignerSyncPower ConsumptionSyncOperating Temperature100 °COperating Temperature-10~50 °C	Pixels	PAL:537Hx597V, NTSC:537Hx505V
S/N Ratiomore than 48dBElectronic Shutter1/50(1/60) - 1/10000 SecFlickerless ModeYesLens3.6 mmGamma Correction0.45Mite Balance (AWB)AutoGain Control (AGC)ON/OFF SelectableBack Light CompensationON/OFF SelectableR24 LEDs, Upto 20 MtrsSyncInternalVideo Output0.9 Vp-p/75 ohmPower Consumption5%Dimensions55 x 92Weight260Operating Temperature-10~50 °C	Resolution	480 TVL
Inspace Inspace   Electronic Shutter 1/50(1/60) - 1/100000 Sec   Flickerless Mode Yes   Lens 3.6 mm   Gamma Correction 0.45   White Balance (AWB) Auto   Gain Control (AGC) ON/OFF Selectable   Back Light Compensation ON/OFF Selectable   Sync Internal   Video Output 1.0 Vp-p/75 ohm   Power Supply DC 12V ± 5%   Power Consumption 75 x 92   Weight 260   Operating Temperature -10~50 °C	Min. Illumination	0 lux @F1.2
Flickerless ModeYesLens3.6 mmGamma Correction0.45White Balance (AWB)AutoGain Control (AGC)ON/OFF SelectableBack Light CompensationON/OFF SelectableBack Light CompensationON/OFF SelectableSyncInternalVideo Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption55 v92Dimensions75 x 92Weight60Operating Temperature-10~50 °C	S/N Ratio	more than 48dB
Lens3.6 mmGamma Correction0.45White Balance (AWB)AutoGain Control (AGC)ON/OFF SelectableBack Light CompensationON/OFF SelectableBack Light CompensationON/OFF SelectableR24 LEDs, Upto 20 MtrsSyncInternalVideo Output1.0 Vp-p/75 ohmPower SupplyC0 12V ± 5%Power Consumption5x 92Dimensions5x 92Weight260Operating Temperature-10~50 °C	Electronic Shutter	1/50(1/60) - 1/100000 Sec
Gamma Correction0.45White Balance (AWB)AutoGain Control (AGC)ON/OFF SelectableBack Light CompensationON/OFF SelectableBack Light Compensation24 LEDs, Upto 20 MtrsInternalInternalVideo Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption5× 92Dimensions75 × 92Operating Temperature-10~C0 °C	Flickerless Mode	Yes
White Balance (AWB)AutoGain Control (AGC)ON/OFF SelectableBack Light CompensationON/OFF SelectableBack Light Compensation24 LEDs, Upto 20 MtrsSyncInternalVideo Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption5× 92Dimensions75 x 92Weight260Operating Temperature-10~50°C	Lens	3.6 mm
Gain Control (AGC)ON/OFF SelectableBack Light CompensationON/OFF SelectableBack Light Compensation24 LEDs, Upto 20 MtrsSyncInternalVideo Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption5X 92Dimensions75 x 92Weight260Operating Temperature-10~50 °C	Gamma Correction	0.45
Back Light CompensationON/OFF SelectableIR24 LEDs, Upto 20 MtrsSyncInternalVideo Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption-5WDimensions75 × 92Weight260Operating Temperature-10~50 °C	White Balance (AWB)	Auto
IR24 LEDs, Upto 20 MtrsSyncInternalVideo Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption<5W	Gain Control (AGC)	ON/OFF Selectable
SyncInternalVideo Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption<5W	Back Light Compensation	ON/OFF Selectable
Video Output1.0 Vp-p/75 ohmPower SupplyDC 12V ± 5%Power Consumption<5W	IR	24 LEDs, Upto 20 Mtrs
Power SupplyDC 12V ± 5%Power Consumption<5WDimensions75 x 92Weight260Operating Temperature-10~50 °C	Sync	Internal
Power Consumption<5WDimensions75 x 92Weight260Operating Temperature-10~50 °C	Video Output	
Dimensions75 x 92Weight260Operating Temperature-10~50 °C	Power Supply	DC 12V ± 5%
Weight260Operating Temperature-10~50 °C	Power Consumption	
Operating Temperature -10~50 °C	Dimensions	75 x 92
	Weight	
Certifications CE, FCC, RoHs	Operating Temperature	-10~50 °C
	Certifications	CE, FCC, RoHs